

# QUANTITA' DI CAVO SU BOBINA

## Lenght each drum

Diametro Bobina (mm) / Drum diameter (mm)	600	800	1000	1200	1400	1600	1800	2000	2200	2500	
	250	600	1300	1700	2500	4000	5000	6000	6500	7000	portata massima in kg / maximum kg each drum
Diametro esterno cavo (mm) / Outer diameter pf cable (mm)	Metri di cavo massimi per bobina / maximum meters each drum										
8,0	1000	2120	4080								
8,5	880	1900	3690								
9,0	780	1700	3210	5410							
9,5	690	1520	2900	4780							
10,0	660	1370	2640	4370							
10,5	580	1230	2390	4000							
11,0	510	1100	2170	3670							
11,5	490	980	1960	3360	5420						
12,0	420	930	1750	3080	5000						
12,5	410	840	1710	2790	4610						
13,0	360	800	1540	2580	4200						
13,5	340	710	1390	2370	3910	5840					
14,0	330	690	1340	2160	3770	5370					
14,5	290	610	1210	2080	3470	4960					
15,0	280	590	1170	1900	3200	4800					
16,0	230	500	1020	1680	2840	4070	5950				
17,0	220	470	880	1480	2540	3630	5000				
18,0	170	400	760	1290	2230	3240	4450	5590			
19,0	160	370	710	1130	2000	2880	4210	5000			
20,0	160	310	630	1090	1770	2570	3760	4750	5680		
21,0	130	300	580	940	1570	2450	3340	4250	5100		
22,0	120	250	510	910	1520	2180	2960	3810	4590		
23,0	120	240	490	800	1350	1940	2820	3390	4110		
24,0		230	410	770	1200	1860	2500	3250	3950	5570	
25,0		190	400	670	1150	1640	2400	2900	3530	5060	
26,0		180	380	640	1010	1580	2110	2790	3390	4590	
27,0		180	320	560	970	1390	2030	2480	3040	4420	
28,0		170	310	540	940	1340	1790	2390	2930	4010	
29,0			300	520	820	1180	1720	2120	2610	3880	
30,0			290	440	800	1140	1670	2040	2527	3510	
31,0			240	430	770	1100	1450	1800	2230	3390	
32,0			230	410	670	960	1400	1740	2170	3070	
33,0			220	400	650	930	1360	1690	2100	2980	
34,0			220	340	630	900	1170	1640	1850	2680	
35,0			210	330	540	880	1140	1430	1800	2600	
36,0			170	320	530	760	1100	1390	1570	2330	
37,0			160	270	510	730	1070	1350	1530	2270	
38,0			160	260	430	710	910	1170	1490	2210	
39,0			160	250	420	610	890	1140	1450	1970	
40,0			150	250	410	590	870	1110	1260	1920	
41,0			150	240	400	580	850	1080	1220	1880	
42,0			110	230	390	560	830	920	1190	1660	
43,0				230	380	550	690	900	1170	1630	
44,0				190	320	540	680	880	1140	1590	
45,0				180	310	450	660	860	970	1550	
46,0				170	300	440	650	840	650	1360	
47,0				170	300	430	630	820	930	1330	
48,0				170	290	410	620	690	910	1310	

# QUANTITA' DI CAVO SU BOBINA

## Lenght each drum

Diametro Bobina (mm) / Drum diameter (mm)	600	800	1000	1200	1400	1600	1800	2000	2200	2500	
	250	600	1300	1700	2500	4000	5000	6000	6500	7000	portata massima in kg / maximum kg each drum
Diametro esterno cavo (mm) / Cable outer diameter (mm)	Metri di cavo massimi per bobina / maximum meters each drum										
49,0				170	290	410	600	680	890	1280	
50,0				160	280	410	500	660	880	1260	
51,0				160	230	400	480	650	860	1090	
52,0				120	230	320	480	640	720	1070	
53,0				120	220	320	470	630	710	1050	
54,0				120	200	310	460	610	700	1030	
55,0					200	300	450	600	680	1010	
56,0					200	300	440	490	670	990	
57,0					200	290	430	480	660	980	
58,0					200	290	430	480	650	840	
59,0					200	280	420	470	640	830	
60,0					200	280	330	460	520	810	
61,0					150	280	320	450	510	800	
62,0					150	220	320	440	500	780	
63,0					150	210	310	440	490	770	
64,0					150	210	310	430	490	760	
65,0					140	200	300	420	480	750	
66,0					140	200	300	420	470	630	
67,0					140	200	290	330	470	620	
68,0					140	200	290	320	460	610	
69,0						190	280	320	450	600	
70,0						190	280	310	440	590	
71,0						180	200	300	350	580	
72,0						180	200	300	340	570	
73,0						130	200	300	340	570	
74,0						130	200	290	330	470	
75,0						130	190	290	330	460	
76,0						130	190	290	320	450	
77,0						130	190	280	320	450	
78,0						130	190	280	320	440	
79,0						120	180	200	310	440	
80,0						120	180	200	310	430	
81,0						120	180	200	300	420	
82,0						120	180	200	300	420	
83,0						110	170	190	300	410	
84,0						110	170	190	290	410	
85,0						110	170	190	290	400	
86,0							170	190	210	400	
87,0							170	190	210	400	
88,0							160	180	210	390	
89,0							160	180	210	310	
90,0							160	180	200	300	
91,0							160	180	200	300	
92,0							160	170	200	300	